




PAR 64 Halogen lamps

Light, bright, cool

A live performance without spotlights? A rock band without a stage show? A discotheque without dazzling light effects? In the entertainment sector, success is largely dependent on a spectacular light show. Therefore, organizers have been relying on PAR lamps for years. Whether used on small or large stages: Our PAR 64 lamps will always be shining stars in show business.

osram.com/entertainment



PAR 64 lamp types

Order reference	64737/4	64738/4	64739/4
ANSI	EXC	EXD	EXE
LIF	CP/60	CP/61	CP/62
Application	Very Narrow Spot	Narrow Spot	Medium Flood
Intended use	 	 	 
Nominal power (W)	1000	1000	1000
On-mode power P _{on} (W)	1030	1030	1030
Rated lamp voltage U (V)	240	240	240
Average service life (h)	300	300	300
Peak luminous intensity (cd)	307,500	255,400	116,000
Colour temperature CTT (K)	3100	3100	3100
Beam angle (°)	12°/9°	14°/10°	24°/11°
Energy efficiency class (A-G)*	G	G	G
Base	GX16d	GX16d	GX16d
Bulb diameter d (mm)	204	204	204
LCL a (mm)	102	102	102
Lamp length l (mm)	152.4	152.4	152.4
Product number	4062172359214	4062172359238	4062172359252

*) The energy label and product information sheet are available on www.osram.com.



PAR 64 lamps are tried and tested when it comes to producing atmosphere at events of any kind.

ams OSRAM Group
ams-osram.com

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany
Phone +49 89-6213-0
Fax +49 89-6213-2020
www.osram.com

Applications

- Events
- Performances
- Stage productions

Features & Benefits

- The parabolic glass reflector and the front lens are fused together
- Easy lamp replacement
- High luminous intensity
- Flexible operating position
- Available in different beam angles to ensure high flexibility